

2009 Wisconsin Energy Efficiency Certificate

(Post on or immediately adjacent to electrical distribution panel)

*Required by SPS 322.20(6)

Insulation Rating

Ceiling/roof _____
 Wall _____
 Floor/Foundation _____
 Ductwork (unconditioned spaces) _____
 Beneath Heated Slab _____
 Perimeter of Heated Slab _____

R-Value

Glass & Door Rating

Window _____
 Skylight _____
 Door _____

U-Factor

Name _____ Date _____

Comments _____

These Efficiency and Compliance Certificates may be used in lieu of the REScheck Certificates

2009 Wisconsin UDC Compliance Certificate

(Submit with building plan submittal)

Owner/Agent _____ Location _____

Heating Appliance Type & Efficiency _____ Zone _____

Building Component	Code Min. Insulation Value (Table 322.31-1)		Code Min. Insulation Value For Lower Efficiency Appliances ¹ (Table 322.31-3)		Enter Actual Insulation Value Proposed
	Zone 1	Zone 2	Zone 1	Zone 2	
Fenestration (U-Value)					
Window	0.35 0.35		0.30	0.30	
Door	0.35 0.35		0.30	0.30	
Skylight (U-Value)	0.60 0.60		0.60	0.60	
Ceiling					
Energy Heel	R-38 R-38		R-38	R-38	
Flat	R-49 R-49		R-49	R-49	
Wood Framed Wall	R-19 or R-13 + R-5	R-21 R-21	or R-19 / R-5	R-21 or R-19 / R-5	
Mass Wall	R-15 R-15		R-19	R-19	
Floor	R-30 R-30		R-30	R-30	
Basement or Crawl Space	R-10 / R-13	R-10 / R-13	R-15 / R-19	R-15 / R-20	
Heated Slab	R-10 / R-15	R-10 / R-15	R-10 / R-20	R-10 / R-20	
Unheated Slab	R-10 R-10		R-15	R-15	

1. Includes less than 90 % efficient natural gas and propane furnaces and hot water boilers, less than 83 % efficient oil-fired furnaces and less than 84% oil-fired hot water heater boilers. (See Table 322.31-3)