

Wisconsin Commercial Building Inspector Certification
Chapter IBC 10 Practice Questions

Practice Sheet 9

Chapter 10

An area where persons unable to use stairways can remain temporarily to await instructions or assistance is called the _____.

An enclosed exit access component that defines and provides a part of egress travel to an exit is referred to as a _____.

What are the three means of egress components _____.

_____ is that portion of a means of egress system between the termination of an exit and public way.

Floor area used to determine occupant load is based on one of two methods which are _____ or _____.

_____ is the continuous and unobstructed path of vertical and horizontal egress travel from any point in a building to a public way.

For areas without fixed seating, the occupant load shall not be less than that number determined by dividing the floor area under consideration by the occupant per unit area factor assigned to the occupancy as set forth in _____.

The maximum designed occupant load based on an assembly space with movable seating is _____.

The maximum floor area allowance per occupant for a business is _____.

The maximum floor area allowance per occupant for the basement of a store is _____.

The occupant load of _____ shall be based on the anticipated use.

Egress width for a stair in a mercantile occupancy will be _____ in an unsprinklered building.

Egress width for a stair in a business occupancy will be _____ in an sprinklered building.

The means of egress shall have a ceiling height of not less than _____.

Where the difference in elevation is _____, the ramp shall be equipped with either handrails or floor finish materials that contrast.

The path of egress travel along a means of egress shall not be interrupted by any building element other than _____.

Exit sign placement shall be such that no point in an exit access corridor is more than _____ from the nearest visible exit sign.

Exit signs can be illuminated either _____.

_____ is the minimum illumination time for an exit sign during primary power loss.

The minimum egress illumination level is _____.

_____ is the minimum illumination time for egress illumination during primary power loss.

Guards are required where the difference in floor levels exceeds _____.

Guards shall for a protective barrier not less than _____ measured _____ from the leading edge of the tread or adjacent walking surface.

Where more than _____ - means of egress is required from any accessible space, each accessible portion of the space shall be served by not less than _____ accessible means of egress.

The minimum clear width of an egress door is _____.

Egress doors shall swing _____ when serving an occupant load of _____ or more.

Stair riser heights shall be _____ and _____.

_____ is the minimum tread depth.

Handrails shall be not less than _____ and not more than _____.