

Wisconsin Commercial Building Inspector Certification
Chapter IBC 10 Practice Questions

Practice Sheet 10

Navigating the Wisconsin Commercial Building Code skill practice sheet. Find the Wisconsin Commercial Building Code section number associated with each of the key words.

Chapter 10 part II

_____ exit or exit access doorway shall be provided from a conference room designed for an occupant load of 50.

_____ exit or exit access doorway shall be provided from a warehouse designed for an occupant load of 35.

Where two exits or exit access doorways are required they shall be placed a distance apart equal to at least _____ the maximum diagonal distance of the building or area.

Where two exits or exit access doorways are required they shall be placed a distance apart equal to at least _____ the maximum diagonal distance of the building or area where the building is fully sprinklered.

Where three or more exits or exit access doorways are required at least _____ will be placed half the diagonal distance apart.

Egress shall not pass through _____ or _____.

Egress _____ permitted to pass through adjoining tenant spaces.

Exit travel distance along an open stair is measured along a plane _____ and _____ to the stair tread nosing in the center of the stair.

Exit travel distance in a sprinklered office building is _____.

Exit travel distance in a unsprinklered grade school is _____.

The exterior egress balcony increase is _____ but the balcony shall not be _____ than the increase taken.

In other than "H" occupancies the maximum common path of egress travel shall not exceed _____.

In a fully sprinklered office building the common path of egress travel shall not exceed _____.

In an office building designed for 30 occupants the common path of egress travel shall not exceed _____.

The minimum clear aisle width of public areas located in a "B" occupancy is _____.

The minimum clear corridor width is _____.

Corridor width can be reduced to _____ where the capacity does not exceed ____ occupants.

A grade school corridor serving 100 or more occupants must be the minimum of _____.

_____ is the maximum dead end corridor length.

Corridors shall not be interrupted by _____.

Once a given level of exit protection is achieved, such level of protection shall not be reduced until arrival at the _____.

Buildings or structures used for human occupancy shall have at least ____ door that meets s. 1008.1.1

A single story factory building with a maximum occupant load of 49 and maximum exit travel distance of 75 feet is permitted to have _____.

Vertical exit enclosures less than _____ stories are required to be _____ fire-resistive construction.

Unenclosed non-required egress stairs shall comply with _____.

Exterior walls of vertical exit enclosures shall comply with _____.

Access to enclosed usable spaces located below exit stairs shall not be directly _____.

The minimum exit passage width is _____.

Exit passageway opening protective shall be in accordance with the requirements of _____.

A _____ shall not be the only exit from any portion of a building.