

Cover policy for Infiltrator chambers in conventional septic system applications.



INFILTRATOR®
systems Inc.

The intent of this policy is to establish cover guidelines for maintaining structural integrity.

During system design it is important to note that any septic system designed and installed deeper than 4 feet may experience performance problems as a result of limited oxygen transfer through the soil.

Depth requirements may vary according to state and local regulations. If unsure of installation requirements, contact your state or local regulators.

Questions regarding the installation of Infiltrator chamber systems? Call the Technical Service Department at 1-800-221-4436 for current installation instructions.

Table 1: Burial depth in feet (exclusive of chamber height)

Configuration	Products				
	Quick4 Standard	Quick4 High Capacity	High Capacity H-20	Quick4 Equalizer 24	Quick4 Equalizer 36
minimum cover in feet					
Beds	0.5/1*	0.5/1*	1.5	0.5/1*	0.5/1*
Trenches**	0.5/1*	0.5/1*	1.5	0.5/1*	0.5/1*
maximum cover in feet					
Beds	4	4	8	4	4
Trenches**	8	8	8	8	8

* 0.5 feet burial depth for non-traffic applications only. 1.0 feet burial depth for H-10 load rating.

** Trenches refers to a 1-foot minimum soil separation between chamber rows.



INFILTRATOR®
systems Inc.

P.O. Box 768 • 6 Business Park Road • Old Saybrook, CT 06475
860-577-7000 • FAX 860-577-7001

www.infiltratorsystems.com

1-800-221-4436

Distributed By: