~~20100136A~~

20140359A

Table 1

ED Model	Sales Model	Max. DWF (gals./day)	Max. BOD5 (lbs./day)	Min. tank capacity upstream (gals.)
100	AS800	300	1.0	250
101	AS1000	600	2.0	500
102	AS1200	900	3.0	750
103	AS1400	1200	3.8	960
104	AS1600	1500	5.5	1200
105	AS1800	1900	7.0	1495

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AERO-STREAM, LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF AERO-STREAM, LLC. MANAGEMENT IS PROHIBITED.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	A	RELEASED FOR QUOTATION	4/5/10	
	B	- REMOVED NTOES RELATED TO FONT TYPE AND SIZE. - NOTE 1 WAS "TEXT TO BE CENTERED ON LABEL". - ADDED G60/G90 TO NOTE 4.	4/15/10	FJS

2.375
2.125

3.375
3.125

ED: ☐100 ☐101 ☐102 ☐103
☐104 ☐105 ☐106 ☐107 ☐108
☐109 ☐110 ☐111 ☐112 ☐113
☐114 ☐115 ☐116 ☐117 ☐118
☐ _____

S/N: _____

Mfg. by: Aero-Stream®, LLC
W300 N7706 Christine La.
Hartland, WI 53029
(262) 538-4000.

C UL US
LISTED
11XP
AIR COMPRESSOR
INDOOR/OUTDOOR USE

☐ .4A ☐ 1.3A
Electrical rating: 120v, 60 Hz, ☐ _____
☐ 1A ☐ 1.8A

WARNING!
Risk of electric shock from back siphoning – locate pump above water level

CAUTION!
Risk of Bursting – Use only recommended air-handling parts acceptable for pressures not less than 8 PSI.

COVERED BY U.S. PATENTS
7,264,727 7,429,320 7,468,135
OTHER PATENTS PENDING

REF. DATE OF MFG. CODE TO BE WRITTEN WITH PERMANENT MARKER AT POINT OF PRODUCT ASSEMBLY. CODE = XXXYYYZZ WHERE XXX=DAY OF YEAR, YY=YEAR, ZZ=DAILY UNIT ASSEMBLY.

UL LOGO PER http://www.ul.com/mark/art.htm#ul
Form Number: 200-195A 20M/11/97

~~201001364~~
20140359A

UNLESS OTHERWISE SPECIFIED:
1.) SEE 102032ART FOR ARTWORK.
2.) MATERIAL: 2.0 MIL MATTE ALUMINUM W/1 PERMANENT ADHESIVE BACKED FOR OUTDOOR APPLICATION PER UL 969.
3.) BLACK INDELIBLE INK PER UL 969.
4.) LABEL TO ADHERE TO HIGH GLOSS PPO (POLYPHENYLENE OXIDE), KORAD ACRYLIC SURFACE AND G60/G90 GALVANIZED CRS PER UL 969.
5.) OPERATING TEMPERATURE RANGE: -10F - 176F.
6.) APPROVED SOURCE: DURATECH IND. CONSTRUCTION TYPE: AF2LU

ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
		PARTS LIST		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
±.015 ±.000 +/- 1
XXX+/-.040

MATERIAL SEE NOTES
FINISH –

NEXT ASSY USED ON
APPLICATION

DO NOT SCALE DRAWING

CAD GENERATED DRAWING. DO NOT MANUALLY UPDATE

APPROVALS		DATE
DRAWN	KKH	4/5/10
CHECKED		
RESP ENG	KKH	
MFG ENG		
QUAL ENG		

AERO-STREAM®, LLC
HARTLAND, WI 53029 262-538-4000

LABEL - QT & AS

SIZE C DWG. NO. 102032 REV. B
SCALE CAD FILE SHEET 1 OF 1

ED: ☐100 ☐101 ☐102 ☐103
☐104 ☐105 ☐106 ☐107 ☐108
☐109 ☐110 ☐111 ☐112 ☐113
☐114 ☐115 ☐116 ☐117 ☐118
☐ _____

S/N: _____

c UL us
LISTED
11XP
AIR COMPRESSOR
INDOOR/OUTDOOR USE

Mfg. by: Aero-Stream® LLC
W300 N7706 Christine La.
Hartland, WI 53029
(262) 538-4000.

Electrical rating: 120v, 60 Hz, ☐.4A ☐1.3A ☐ _____ ☐1A ☐1.8A

WARNING!
Risk of electric shock from back siphoning – locate pump above water level

CAUTION!
Risk of Bursting – Use only recommended air-handling parts acceptable for pressures not less than 8 PSI.

COVERED BY U.S. PATENTS
7,284,727 7,429,320 7,468,135
OTHER PATENTS PENDING

~~20100064~~
20140359A