



Scott McCallum, Governor
Philip W. Albert, Acting Secretary

October 25, 2001

SEARS ROEBUCK AND COMPANY
KENMORE
SANDRA L. GAMES
PO BOX 64420
SAINT PAUL MN 55164-0421

Re: Description: WATER TREATMENT DEVICE-ACTIVATED CARBON
Manufacturer: SEARS ROEBUCK AND COMPANY
Product Name: KENMORE DELUXE DUAL STAGE DRINKING WATER SYSTEM
Model Number(s): 625.384650 USING THE 42-38466 CARTRIDGE SET
Product File No: 20010218

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters Comm 82 through 84, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an approval based on the Wisconsin Statutes and the Wisconsin Administrative Code. This approval is valid until the end of October 2006.

This approval is contingent upon compliance with the following stipulation(s):

- This product has undergone sufficient testing to document the product's ability to reduce only those contaminants and/or substances as specified in this approval letter when the product is installed and maintained in strict accordance with the manufacturers published instructions.
- For buildings not served by a municipal water supply, Department of Natural Resources (DNR) written approval may be required prior to installation of this product in a water supply system to reduce the concentration of a contaminant that exceeds the primary drinking water standards contained in ch. NR 809, Wis. Admin. Code, the enforcement standards contained in ch. NR 140, Wis. Admin. Code, or for a water supply system that is subject to a written advisory opinion by the DNR. For more information contact the DNR Section of Private Water Systems, P.O. Box 7921, Madison, WI 53707, telephone (608) 266-3415.
- If this approved device is modified or additional assertions of function or performance are made, then this approval shall be considered null and void, unless the change is submitted to the department for review and the approval is reaffirmed.

Based on testing data submitted to and reviewed by the department, this approval recognizes that this plumbing product will reduce the concentration of contaminants as specified on pages 1 through 4 of this letter and tables 1 of 4 through 4 of 4.

**HEALTH EFFECTING INORGANIC CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20010218
 TABLE 1 OF 4**

Flow Rate: 2.3 Liters per minute (Lpm) [0.6 gallons per minute (gpm)]

Capacity: 3,937 Liters (L) [1,040 gallons (gals.)] for lead reduction. For asbestos reduction, the capacity is dependent on the type and quantity of particulate matter present in the influent water; the need for maintenance may be indicated by a significant decrease in flow rate.

Tested Contaminant	Tested Influent Concentration (mg/L) ¹
Asbestos fibers (> 10 µm in length)	1.0 x 10 ⁷ to 1.0 x 10 ⁸ F/L
Lead (Pb ⁺²) ²	0.15 ± 10%

Other conditions: the contaminant reduction capabilities displayed for table 1 of 4 were generated by testing conducted in accordance with NSF *International* Standard 53. To qualify for asbestos reduction, the device must reduce the influent challenge concentrations by ≥ 99%. To qualify for lead reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 0.010 mg/L.

1 = milligrams per liter (mg/L) are equivalent to parts per million (ppm)

2 = metals are tested at pH 6.5 and pH 8.5

≤ = less than or equal to

* = unless otherwise indicated

± = plus or minus

≥ = greater than or equal to

F/L = fibers per liter

**HEALTH EFFECTING BIOLOGICAL CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20010218
 TABLE 2 OF 3**

Flow Rate: 2.3 Lpm (0.6 gpm)

Capacity: dependent on the type and quantity of particulate matter present in the influent water; the need for maintenance may be indicated by a significant decrease in flow rate.

Tested Contaminant	Influent Challenge (#/mL)
Cysts/Oocysts ¹	≥ 5.0 x 10 ⁴

Other Conditions: the contaminant reduction performance capabilities displayed for Table 2 of 3 were verified by testing conducted in accordance with NSF *International* Standard 53. To qualify for cyst/oocyst reduction, the device must reduce the influent challenge concentrations by ≥ 99.95% at each sample point.

1 = the specific organisms covered under this testing protocol include cryptosporidium parvum, entamoeba histolytica, giardia lamblia and toxoplasma gondii

≥ = greater than or equal to

#/mL = particles per milliliter

**AESTHETIC INORGANIC CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20010218
 TABLE 3 OF 4**

Flow Rate: 2.3 Lpm (0.6 gpm)

Capacity: 3,937 L (1,040 gals.)

Tested Contaminant	Tested Influent Concentration (mg/L) ¹
Chlorine (free)	2.0 ± 10%

Other conditions: the contaminant reduction capabilities displayed for table 3 of 4 were generated by testing conducted in accordance with NSF *International* Standard 42. To qualify for free chlorine reduction (Class I), the device shall reduce the influent challenge concentrations by ≥ 75%.

1 = milligrams per liter (mg/L) are equivalent to parts per million (ppm)

≥ = greater than or equal to

± = plus or minus

**HEALTH EFFECTING ORGANIC CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20010218
 TABLE 4 OF 4**

Flow Rate: 2.3 Lpm (0.6 gpm)
Capacity: 3,937 L (1,040 gals.)

Tested Contaminant	Influent Challenge (µg/L) [†]
Alachlor	50
Atrazine	100
Benzene	81
Carbofuran	190
Carbon tetrachloride	78
Chlorobenzene	77
Chloropicrin	15
2,4-D	110
Dibromochloropropane (DBCP)	52
o-Dichlorobenzene	80
p-Dichlorobenzene	40
1,2-Dichloroethane	88
1,1-Dichloroethylene	83
cis-1,2-Dichloroethylene	170
trans-1,2-Dichloroethylene	86
1,2-Dichloropropane	80
cis-1,3-Dichloropropylene	79
Dinoseb	170
Endrin	53
Ethylbenzene	88
Ethylene dibromide (EDB)	44
Haloacetonitriles (HAN):	-
Bromochloroacetonitrile	22
Dibromoacetonitrile	24
Dichloroacetonitrile	9.6
Trichloroacetonitrile	15
Haloketones (HK):	-
1,1-Dichloro-2-propanone	7.2
1,1,1-Trichloro-2-propanone	8.2
Heptachlor	25
Heptachlor epoxide	10.7
Hexachlorobutadiene	44
Hexachlorocyclopentadiene	60
Lindane	55
Methoxychlor	50
Methyl <i>tert</i> -butyl ether (MtBE) [†]	15 ± 20%
Pentachlorophenol	96
Simazine	120
Styrene	150
1,1,2,2-Tetrachloroethane	81
Tetrachloroethylene	81
Toluene	78
2,4,5-TP (silvex)	270
Tribromoacetic acid	42
1,2,4-Trichlorobenzene	160
1,1,1-Trichloroethane	84
1,1,2-Trichloroethane	150
Trichloroethylene	180

HEALTH EFFECTING ORGANIC CONTAMINANT REDUCTION CAPABILITIES (continued)
PRODUCT FILE NUMBER 20010218
TABLE 4 OF 4

Tested Contaminant	Influent Challenge (µg/L)¹
Trihalomethanes	-
chloroform (surrogate chemical)	300
bromoform	-
bromodichloromethane	-
chlorodibromomethane	-
Xylenes (total)	70

Other Conditions: the contaminant reduction performance capabilities displayed for Table 4 of 4 were verified by testing conducted in accordance with NSF *International* Standard 53. To qualify for the reduction of the organic contaminants listed above, the device must reduce the influent challenge concentration of chloroform at 300 µg/L ± 10% at each sample point by a minimum of 95%. To qualify for MtBE reduction, the class must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 5.0 µg/L.

1 = micrograms per liter (µg/L) are equivalent to parts per billion (ppb) ± = plus or minus
† = tested independently of the chloroform surrogate ≤ = less than or equal to

If these approved devices are modified or additional assertions of function or performance are made, then this approval shall be considered null and void, unless the change is submitted to the department for review and the approval is reaffirmed.

The department is in no way endorsing this product or any advertising, and is not responsible for any situation that may result from its use.

Sincerely,

Glen W. Schlueter
Engineering Consultant-Plumbing Product Reviewer
Bureau of Integrated Services
Safety and Buildings Division
Department of Commerce
(608) 267-1401 **Phone**
(608) 267-9566 **Fax**
gschlueter@commerce.state.wi.us **Email**
9:00A – 5:00P CDT **Work Hours**
GWS:gws