



January 14, 2003

MULTI-PURE CORPORATION
PAULA RICE
7251 CATHEDRAL ROCK DRIVE
LAS VEGAS NV 89128

Re: Description: WATER TREATMENT DEVICE-ACTIVATED CARBON
Manufacturer: MULTI-PURE CORPORATION
Product Name: MULTI-PURE
Model Number(s): MP1200EL USING THE CB6 CARTRIDGE
Product File No: 20020456

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters Comm 82 through 84, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an approval based on the Wisconsin Statutes and the Wisconsin Administrative Code. This approval is valid until the end of January 2008.

This approval supercedes the approval issued on November 3, 1997 under product file number 19970353.

This approval is contingent upon compliance with the following stipulation(s):

- This product has undergone sufficient testing to document the product's ability to reduce only those contaminants and/or substances as specified in this approval letter when the product is installed and maintained in strict accordance with the manufacturers published instructions.
- For buildings not served by a municipal water supply, Department of Natural Resources (DNR) written approval may be required prior to installation of this product in a water supply system to reduce the concentration of a contaminant that exceeds the primary drinking water standards contained in ch. NR 809, Wis. Admin. Code, the enforcement standards contained in ch. NR 140, Wis. Admin. Code, or for a water supply system that is subject to a written advisory opinion by the DNR. For more information contact the DNR Section of Private Water Systems, P.O. Box 7921, Madison, WI 53707, telephone (608) 266-3415.
- If these approved devices are modified or additional assertions of function or performance are made, then this approval shall be considered null and void, unless the change is submitted to the department for review and the approval is reaffirmed.

Based on testing data submitted to and reviewed by the department, this approval recognizes that these plumbing products will reduce the concentration of contaminants as specified on pages 1 through 4 of this letter and table 1 of 4 through 4 of 4.

**HEALTH EFFECTING ORGANIC CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20020456
 TABLE 1 OF 4**

Flow Rate: 2.8 liters per minute (lpm) [0.75 gallons per minute (gpm)]
Capacity: 4,542.5 liters (l) [1,200 gallons (gals.)]

Tested Contaminant	Influent Challenge (µg/L) ¹
Alachlor	50
Atrazine	100
Benzene	81
Carbofuran	190
Carbon tetrachloride	78
Chlordane [‡]	40 ± 10%
Chlorobenzene	77
Chloropicrin	15
2,4-D	110
Dibromochloropropane (DBCP)	52
o-Dichlorobenzene	80
p-Dichlorobenzene	40
1,2-Dichloroethane	88
1,1-Dichloroethylene	83
cis-1,2-Dichloroethylene	170
trans-1,2-Dichloroethylene	86
1,2-Dichloropropane	80
cis-1,3-Dichloropropylene	79
Dinoseb	170
Endrin	53
Ethylbenzene	88
Ethylene dibromide (EDB)	44
Haloacetonitriles (HAN):	-
Bromochloroacetonitrile	22
Dibromoacetonitrile	24
Dichloroacetonitrile	9.6
Trichloroacetonitrile	15
Haloketones (HK):	-
1,1-Dichloro-2-propanone	7.2
1,1,1-Trichloro-2-propanone	8.2
Heptachlor (H-34, HEPTOX)	80
Heptachlor epoxide	10.7
Hexachlorobutadiene	44
Hexachlorocyclopentadiene	60
Lindane	55
Methoxychlor	50
Methyl <i>tert</i> -butyl ether (MtBE) [‡]	15 ± 20%
Pentachlorophenol	96
Polychlorinated biphenyls (PCB's, arochlor 1260) [‡]	10 ± 10%
Simazine	120
Styrene	150
1,1,2,2-Tetrachloroethane	81
Tetrachloroethylene	81
Toluene	78
Toxaphene [‡]	15 ± 10%
2,4,5-TP (silvex)	270
Tribromoacetic acid	42
1,2,4-Trichlorobenzene	160
1,1,1-Trichloroethane	84
1,1,2-Trichloroethane	150
Trichloroethylene	180
Trihalomethanes (chloroform surrogate)	300
Xylenes (total)	70

**HEALTH EFFECTING ORGANIC CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20020456
 TABLE 1 OF 4 (continued)**

Other Conditions: the contaminant reduction performance capabilities displayed for Table 1 of 4 were verified by testing conducted in accordance with NSF *International* Standard 53. To qualify for the reduction of the organic contaminants listed above, the device must reduce the influent challenge concentration of chloroform at 300 µg/L ± 10% at each sample point by a minimum of 95%. To qualify for chlordane reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 2.0 µg/L. To qualify for MtBE reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 5.0 µg/L. To qualify for PCB reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 0.5 µg/L. To qualify for toxaphene reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 3.0 µg/L.

1 = micrograms per liter (µg/L) are equivalent to parts per billion (ppb) ‡ = tested independently of the chloroform surrogate
 ≤ = less than or equal to

**AESTHETIC CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20020456
 TABLE 2 OF 4**

Flow Rate: 2.8 liters per minute (lpm) [0.75 gallons per minute (gpm)]
Capacity: 4,542.5 liters (l) [1,200 gallons (gals.)] for the reduction of chloramines and free chlorine. For particulate reduction, dependent on the type and quantity of particulate matter present in the influent water; the need for maintenance may be indicated by a significant decrease in flow rate.

Tested Contaminant	Influent Challenge (mg/L)* ¹
Chloramines (monochloramine as Cl ₂ /L)	3.0 ± 10%
Chlorine (free)	2.0 ± 10%
Particulates (0.5 to < 1.0 µm)	1.0 x 10 ⁴ #/mL

Other Conditions: the contaminant reduction performance capabilities displayed for Table 2 of 4 were verified by testing conducted in accordance with NSF *International* Standard 42. To qualify for chloramine reduction, the device must reduce the influent challenge concentrations such that prior to the 100% sample point, 90% of the effluent samples contain ≤ 0.5 mg/L chloramine; samples collected at the 100% sample point must be ≤ 0.5 mg/L chloramine. To qualify for free chlorine reduction the device must reduce the influent challenge concentrations by ≥ 75% at each sample point. To qualify for particulate reduction (Class I), the device must reduce the influent challenge concentration by ≥ 85%.

1 = milligrams per liter (mg/L) are equivalent to parts per million (ppm) < = less than
 ≥ = greater than or equal to µm = micrometers
 * = unless otherwise specified #/mL = particles per milliliter
 ± = plus or minus

**HEALTH EFFECTING BIOLOGICAL CONTAMINANT REDUCTION CAPABILITIES
 PRODUCT FILE NUMBER 20020456
 TABLE 3 OF 4**

Flow Rate: 2.8 liters per minute (lpm) [0.75 gallons per minute (gpm)]
Capacity: dependent on the type and quantity of particulate matter present in the influent water; the need for maintenance may be indicated by a significant decrease in flow rate.

Tested Contaminant	Influent Challenge (#/mL)
Cysts/Oocysts ¹	≥ 5.0 x 10 ⁴

Other Conditions: the contaminant reduction performance capabilities displayed for Table 3 of 4 were verified by testing conducted in accordance with NSF *International* Standard 53. To qualify for cyst/oocyst reduction, the device must reduce the influent challenge concentrations by ≥ 99.95% at each sample point.

1 = the specific organisms covered under this testing protocol include cryptosporidium parvum, entamoeba histolytica, giardia lamblia and toxoplasma gondii
 #/mL = particles per milliliter ≥ = greater than or equal to

**HEALTH EFFECTING INORGANIC CONTAMINANT REDUCTION CAPABILITIES
PRODUCT FILE NUMBER 20020456
TABLE 4 OF 4**

Flow Rate: 1.9 Liters per minute (Lpm) [0.5 gallon per minute (gpm)]
Capacity: For asbestos reduction, dependent on the type and quantity of particulate matter present in the influent water; the need for maintenance may be indicated by a significant decrease in flow rate. For lead and mercury, the capacity is 4,542.5 liters (l) [1,200 gallons (gals.)]

Tested Contaminant	Influent Challenge Concentration (mg/L) ¹
Asbestos Fibers (> 10µm in length)	1.0 x 10 ⁷ to 1.0 x 10 ⁸ F/L
Lead (Pb ⁺²) ²	0.15 ± 10%
Mercury (Hg ⁺²) ²	0.006 ± 10%

Other Conditions: the contaminant reduction performance capabilities displayed for Table 4 of 4 were verified by testing conducted in accordance with NSF *International* Standard 53. To qualify for asbestos reduction, the device must reduce the influent challenge concentrations by ≥ 99%. To qualify for lead reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 0.010 mg/L. To qualify for mercury reduction, the device must reduce the influent challenge concentrations such that all effluent concentrations are ≤ 0.002 mg/L.

1 = milligrams per liter (mg/L) are equivalent to parts per million (ppm)
F/L = fibers per liter
≤ = less than or equal to
± = plus or minus

2 = metals are tested at pH 6.5 and pH 8.5
* = unless otherwise specified
≥ = greater than or equal to

This device was tested under controlled laboratory, or field, conditions. The actual performance of this device for a specific end use installation will vary from the tested conditions based on local factors such as water pressure, water temperature and water chemistry.

The department is in no way endorsing this product or any advertising, and is not responsible for any situation that may result from its use.

Sincerely,

Glen W. Schlueter
Engineering Consultant-Plumbing Product Reviewer
Bureau of Integrated Services
Safety and Buildings Division
Department of Commerce
(608) 267-1401 **Phone**
(608) 267-9566 **Fax**
gschlueter@commerce.state.wi.us **Email**
8:00A – 4:30P CT **Work Hours**

GWS:gws