



January 10, 2011

WATER QUALITY ASSOCIATION
PRODUCT CERTIFICATION
TINA FISCHER
4151 NAPERVILLE RD
PO BOX 3696
LISLE IL 60532-3696

CULLIGAN INTERNATIONAL
JOHN BEAVER
9399 W. HIGGINS ROAD, STE 1100
ROSEMONT IL 60018

Re: Description: WATER TREATMENT DEVICE- MECHANICAL
Manufacturer: CULLIGAN INTERNATIONAL
Product Name: CULLIGHAN HIGH EFFICIENCY (POE)
Model Number(s): 9-INCH FILTER CLEER (POE)
Product File No: 20100478

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters Comm 82 through 84, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an approval based on the Wisconsin Statutes and the Wisconsin Administrative Code. This approval is valid until the end of January 2016.

This approval is contingent upon compliance with the following stipulation(s):

- This product has undergone sufficient testing to document the product's ability to reduce only those contaminants and/or substances as specified in this approval letter when the product is installed and maintained in strict accordance with the manufacturer's published instructions.
- Where the Department of Natural Resources (DNR) has jurisdiction, a written approval may be required prior to installation of this product in a water supply system to reduce the concentration of a contaminant that exceeds the primary drinking water standards contained in ch. NR 809, Wis. Admin. Code, the enforcement standards contained in ch. NR 140, Wis. Admin. Code, or for a water supply system that is subject to a written advisory opinion by the DNR. For more information contact the DNR Section of Private Water Systems, P.O. Box 7921, Madison, WI 53707, telephone (608) 267-9787.
- If this approved device is modified or additional assertions of function or performance are made, then this approval shall be considered null and void, unless the change is submitted to the department for review and the approval is reaffirmed.

Based on testing data submitted to and reviewed by the department, this approval recognizes that this plumbing product will reduce the concentration of contaminants as specified on pages 1 through 2 of this letter.

**AESTHETIC CONTAMINANT REDUCTION CAPABILITIES
PRODUCT FILE NUMBER 20100478
TABLE 1 OF 1**

Flow Rate: 34.1 liters per minute (lpm) [9.0 gallon per minute (gpm)]
Capacity: For particulate reduction the capacity is dependent on the type and quantity of particulate matter present in the untreated water; the need for maintenance may be indicated by a significant decrease in flow rate.

Tested Contaminant	Influent Challenge (#/ml)
Particulates (≥ 30 to $< 50 \mu\text{m}$)	$\geq 1.0 \times 10^4$

Other Conditions: the contaminant reduction performance capabilities displayed for Table 1 of 1 were verified by testing conducted in accordance with NSF *International* Standard 42. To qualify for particulate reduction (Class I) the device must reduce the influent challenge concentrations by $\geq 85\%$.

$<$ = less than

\geq = greater than or equal to

\pm = plus or minus

μm = micrometers

$\#/ml$ = particles per milliliter

This device was tested under controlled laboratory, or field, conditions. The actual performance of this device for a specific end use installation will vary from the tested conditions based on local factors such as water pressure, water temperature and water chemistry.

The department is in no way endorsing this product or any advertising, and is not responsible for any situation which may result from its use.

Sincerely,

Glen W. Schlueter
Engineering Consultant-Plumbing Product Reviewer
Bureau of Integrated Services
Safety and Buildings Division
Department of Commerce
(608) 267-1401 **Phone**
(608) 267-9566 **Fax**
glen.schlueter@wi.gov **Email**
8:00AM – 4:30PM CT **Work Hours**
GWS:gws