



August 9, 2012

CULLIGAN INTERNATIONAL
YE LIU
9399 W. HIGGINS ROAD, STE 1100
ROSEMONT IL 60018

Re: Description: WATER TREATMENT DEVICE - POE NEUTRALIZING
Manufacturer: CULLIGAN INTERNATIONAL
Product Name: CULLIGAN MEDALLIST CULLNEU FILTERS
Model Number(s): 8-INCH AND 10-INCH
Product File No: 20120227

The specifications and/or plans for this plumbing product have been reviewed and determined to be in compliance with chapters SPS 382 through 384, Wisconsin Administrative Code, and Chapters 145 and 160, Wisconsin Statutes.

The Department hereby issues an approval based on the Wisconsin Statutes and the Wisconsin Administrative Code. This approval is valid until the end of August 2017.

This approval supersedes the approval issued on November 16, 2007 under product file number 20070494.

This approval is contingent upon compliance with the following stipulation(s):

- This product has undergone sufficient testing to document the product's ability to reduce only those contaminants and/or substances as specified in this approval letter when the product is installed and maintained in strict accordance with the manufacturer's published instructions.
- Where the Department of Natural Resources (DNR) has jurisdiction, a written approval may be required prior to installation of this product in a water supply system to reduce the concentration of a contaminant that exceeds the primary drinking water standards contained in ch. NR 809, Wis. Admin. Code, the enforcement standards contained in ch. NR 140, Wis. Admin. Code, or for a water supply system that is subject to a written advisory opinion by the DNR. For more information contact the DNR Section of Private Water Systems, P.O. Box 7921, Madison, WI 53707, telephone (608) 267-9787.
- If these approved devices are modified or additional assertions of function or performance are made, then this approval shall be considered null and void, unless the change is submitted to the department for review and the approval is reaffirmed.

Based on testing data submitted to and reviewed by the department, this approval recognizes that these plumbing products will reduce the concentration of contaminants as specified on pages 1 through 2 of this letter.

**AESTHETIC CONTAMINANT REDUCTION CAPABILITIES
PRODUCT FILE NUMBER 20120227
TABLE 1 OF 1**

Rated Service Flow Rates:

8-inch Cullneu = 10.2 lpm @ 3.0 psig [2.7 gallons per minute (gpm) @ 3.0 psig]
10-inch Cullneu = 15.1 lpm @ 4.0 psig (4.0 gpm @ 4.0 psig)

Capacities, liters (l):

8-inch Cullneu = 51,103 l [13,500 gallons (gals.)]
10-inch Cullneu = 75,708 l (20,000 gals.)

Tested Contaminant	Influent Challenge
pH (low)	4.0 ± 0.5 pH units

Other Conditions: the contaminant reduction performance capabilities displayed for Table 1 of 1 were verified by testing conducted in accordance with WQA Standard S-200. To qualify for pH modification, the device must increase the influent challenge pHs' such that all effluent pHs' are ≥ 6.5 and ≤ 8.5 . The treatment media is sacrificial (i.e. consumed in the treatment process) so it will require replenishment from time to time.

\geq = greater than or equal to \pm = plus or minus
 \leq = less than or equal to

This device was tested under controlled laboratory, or field, conditions. The actual performance of this device for a specific end use installation will vary from the tested conditions based on local factors such as water pressure, water temperature and water chemistry.

The department is in no way endorsing this product or any advertising, and is not responsible for any situation which may result from its use.

Sincerely,

Glen W. Schlueter
Engineering Consultant
Safety and Buildings Division
Department of Safety and Professional Services
(608) 267-1401 Phone
(608) 267-9566 Fax
glen.schlueter@wi.gov Email
7:30AM - 4:30PM CT Work Hours

GWS:gws