## Industry Services Division Department of Safety and Professional Services

## Steam Heating Boiler Checklist

Owner:	Location:	
Tag / Registration No : B		

Boiler Attributes			
TYPE			
USE	HWH PRO StmHT PWR HtHW OTH		
MFGR			
ID	NB: SERIAL#:		
YEAR			
CAPACITY	Lbs/Hr:		
FIRING	Hand: Auto: Stkr: Oth:		
FUEL	Ng_Oil_ Elec_ Wood_ Coal_ LP_ Blk Lq_		
MAWP			
SRV	Set:		
Internal Hydr			
-			
HOT WATER HEA	ATING COMMENTS		
Code Section	Item Description		
SPS 341.41 (1)	SBD-6314 SUBMITTED		
SPS 305.70	VALID HVAC CONTRACTOR REG.		
SPS 341.42 ref.	ASME NAMEPLATE ATTACHED		
NBIC			
SPS 341.17(4)	SAFETY VALVE (Annual test required)		
SPS 341.42	1. SET PRESSURE ( ) PSI		
SPS 341.42	2. CAPACITY ( )LB/HR		
HG-701.1	3. VERTICALLY MOUNTED		
SPS 341.42	4. "HV" or "VR" STAMPING w / SEAL		
SPS 341.42 /HG-	5. DISCHARGE PIPING		
701.6			
SPS 341.42 /HG-	STEAM PRESSURE GAGE -SIPHON		
602			
SPS 341.42/HG-	STEAM PRESSURE GAGE GRADUATION		
602(b)			
SPS 341.42 /HG-	WATER / GAGE GLASS		
603			
SPS 341.42/HG-	WATER COLUMN PIPING		
604			
SPS 341.42/HG-	PRESSURE CONTROLS		
605	A VYCYA D GT		
SPS 341.42/HG-	1. HIGH LIMIT		
605	2. ODED ATTINIC LIN OTT		
SPS 341.42/HG-	2. OPERATING LIMIT		
605 SPS 341.42/HG-	2. SEDADATE CONTROL CONNECT		
	3. SEPARATE CONTROL CONNECT.		
605 SPS 341.42/HG-	LOW WATER CUT-OFF		
	LUW WAIER CUI-UFF		
614 SPS 341.42/HG-	1. PIPING AT PROPER LEVEL		
	I. FIFING AT FROPER LEVEL		
614			

## Industry Services Division Department of Safety and Professional Services

## Steam Heating Boiler Checklist

	<u> </u>	
SPS 341.42/HG-	2. DRAINAGE / TESTING	
614		
SPS 341.42/HG-	3. TEST-SATISFACTORY OPERATION	
614		
SPS 341.42/HG-	ISOLATION STOP VALVES	
710.4		
SPS 341.42/HG-	1. STEAM STOP	
710.1		
SPS 341.42/HG-	2. RETURN STOP	
710.1		
SPS 341.42/HG-	FEED WATER CONNECTION	
703		
SPS 341.42/HG-	1. STOP VALVE / CHECK VALVE	
705(a)		
SPS 341.42/HG-	2. HARTFORD – EQUALIZING LOOP	
614		
SPS 382.21	3. BACK-FLO PREVENTER	_
SPS 341.42/HG-	4. ACCEPTABLE INTRO. TO BOILER	
705	DI OWI DOWN LIVE IN THE	
SPS 341.42/HG-	BLOW DOWN VALVES	
715(a)	1. DDEGGLIDE WELLD DAWED	
SPS 341.42/HG-	1. PRESSURE TEMP RATED	
715(d)	A CUZED DDODEDLY	
SPS 341.42/HG-	2. SIZED PROPERLY	
715(c) SPS 341.42/HG-	3. TERMINATE AT SAFE LOCATION	
715	5. TERMINATE AT SAFE LOCATION	
SPS 341.42/41.19	INSPECTION OPENINGS	
SPS 341.42/41.19	1. MANHOLE	
SPS 341.19	2. HANDHOLE	
HG-725	FOUNDATION / SETTINGS	
SPS 341.37	MAINTENACE	
SPS 341.37(3)	MODIFICATION OF BOILER BURNER	
SFS 541.57(5)	ASSEMBLY REPORT ON SBD-6314	
SPS 341.38(3)	FUEL CONVERSIONS REPORTED ON	
51 5 571.50(5)	SBD-6314	
SPS 341.38(4)	CHANGE IN BURNER "HEAT INPUT"	+
DI D 341.30(4)	REPORTED ON FORM SBD-6314	
HG-634	REMOTE CONTROLS	+
IBC 64.0503	BREECHING / EXHAUST VENTING	+
NFPA-54	BURNER & FUEL PIPING	
IBC 64.0700	COMBUSTION AIR	
IDC 04.0700	COMBOSTION AIR	